

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : **03-288699**

(43)Date of publication of application : **18.12.1991**

---

(51)Int.Cl.

B44C 1/17  
B29C 45/14

---

(21)Application number : **02-091148**

(71)Applicant : **TOPPAN PRINTING CO LTD**

(22)Date of filing : **05.04.1990**

(72)Inventor : **TAKAGI TAKASHI**  
**AZUMA MASANOBU**

---

### (54) TRANSFER FOIL

#### (57)Abstract:

**PURPOSE:** To sufficiently follow even a molded product whose corner parts have a small R by deep drawing by successively providing a separating layer consisting of a release varnish layer, a pattern layer and an adhesive layer to a film formed by biaxially stretching specific polyethylene terephthalate.

**CONSTITUTION:** As a base sheet, a polyester film whose thickness is set to at least 30 $\mu$ m formed by biaxially stretching polyethylene terephthalate obtained by adding a resin avoiding crystallization at the time of the polycondensation of terephthalic acid and ethylene glycol is used. A release varnish layer is provided in 1 $\mu$ m thickness from a low temp. baking type acrylic polyol resin and a pattern layer is formed using ink containing an urethane resin and an adhesive layer is provided in 1.8 $\mu$ m thickness from acrylic adhesive varnish. Next, the transfer foil constituted as mentioned above is used to apply in-mold transfer processing to a tray-shaped molded product using a styrene resin or an acrylic resin and the release varnish layer being a separation layer is separated to remove the base sheet.

---

### LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]